



**ALLTER**

ALTERNATE  
CORROSION  
PREVENTION  
SYSTEMS



# ALLTER GEOTEX

## PRODUCT DATA SHEET

### Selection and Specification Data

<b>Generic Type</b>	Strong polyolefin woven geotextile fabric.
<b>Product Description</b>	Separation layer, disconnecting ALLTER Putty & ALLTER Mechanical protective layers in odd shaped and difficult to coat objects.
<b>Features</b>	<ul style="list-style-type: none"><li>• Highly impermeable,</li><li>• Allows CP current to pass, does not shield,</li><li>• extra mechanical protection,</li><li>• environmental friendly,</li><li>• Easy to shape.</li></ul>
<b>Benefits</b>	<ul style="list-style-type: none"><li>• Harmless to environment and workers</li><li>• Fast &amp; Easy to apply</li><li>• Additional impact resistance</li><li>• Object can easily be controlled before and after application<ul style="list-style-type: none"><li>○ ALLTER VE Putty can be re-used after removal</li></ul></li></ul>
<b>Color</b>	Black
<b>Volume Solids</b>	100%
<b>Application examples</b>	<ul style="list-style-type: none"><li>• Odd shaped Parts such as flanges, valves, manhole covers, transitions etc.</li><li>• Field joints &amp; Pipeline sections acting as extra protection over ALLTER Mechanical Protective solutions, ALLTER Tape PE / PVC / ALLTER Glass Shield etc, as anti-soil stress catching system</li></ul>

## Cleanup and Safety Information

<b>Cleanup</b>	NR
<b>Safety</b>	Product does not contain any hazardous ingredients.

## Packaging, Handling and Storage

<b>Shelf life</b>	Unlimited at 23°C (73°F)
<b>Storage temperature and humidity</b>	4 - 50°C (39-122°F). 85%.
<b>Packaging</b>	Roll 100m <sup>2</sup> / Sheets (cut to size upon request)
<b>Storage</b>	Material should be stored indoors, clean and dry.
<b>Ignition temp.</b>	>300°C

**DATE: January 2024**

**DISCLAIMER:** Allter Coatings warrants that the product(s) represented within conform(s) to its/their chemical and physical description and is appropriate for the use as stated on the respective technical data sheet when used in compliance with Allter Coatings written instructions. Since many installation factors are beyond the control of Allter Coatings the user is obligated to determine the suitability of the products for the intended use and assume all risks and liabilities in connection herewith. Allter Coatings liability is stated in the standard terms and conditions of sale. Allter Coatings makes no other warranty either expressed or implied. All information contained in the respective technical data sheet(s) should be used as a guide and is subject to change without notice. This document supersedes all previous revisions. Please see revision date on the left. Allter® is a registered trademark.